



9	KEY	CARBON STEEL	1
8	GEAR	Cast iron	1
7	INDICATOR	CARBON STEEL	1
6	O-RING	EPDM	1
5	BUSHING	PTFE	4
4	STEM	SS416	1
3	SEAT	NBR	1
2	DISC	ALUMINUM BRONZE	1
1	BODY	A216 WCB	1
NO. PARTS NAME MATERIAL			QTY

8"	160	205	45	298.5	295	295	102	125	22.2	8-22	8-22	12-22	4-11.5	60
10"	196	246	45	362.0	350	355	102	125	28.6	12-25	12-22	12-26	4-11.5	-
12"	220	270	45	431.8	400	410	102	125	31.7	12-25	12-22	12-26	4-11.5	-
14"	256	316	45	476.3	460	470	102	125	31.7	12-28	16-22	16-26	4-11.5	-
16"	308	365	51	539.8	515	525	165	210	33.34	16-28	16-26	16-30	4-22.2	-
18"	335	390	51	577.9	565	585	165	210	38	16-32	20-26	20-30	4-22.2	-
20"	360	415	64	635.0	620	650	165	210	41.15	20-32	20-26	20-33	4-22.2	-
24"	426	510	70	749.3	725	770	165	210	50.65	20-35	20-30	20-36	4-22.2	-
SIZE	A	B	C	150Lbs	PN10	PN16	ØE	ØF	ØG	150Lbs	PN10	PN16	4-Ød1	L
				ØD						n-Ød				

TEST PRESSURE	HYDROSTATIC	SHELL	24 kg/cm ²	SEAL	17.6 kg/cm ²
	AIR				
STAND-ARD	DESIGN CODE			API 609	
	INSPECTION & TEST			API598	
	END STANDARD			ANSI150/PN10/PN16	
	FACE TO FACE			API609	
TITLE :LEVER WAFER BUTTERFLY VALVE DN200-DN600					
APPROVED			DWG NO.		REV
CHECKED					
DRAWN					
DESIGNED			SCALE	UNIT	mm
SIGNATURE					